

# BM Transformer / Coil Winding Machines

---

<http://www.whitelegg.com/products/coil-winding/electric-motor-rewind-and-repair/bm-transformer-coil-winding-machines-9fab93b9-6c42-4236-a43f-918848363f65>

---

**The BM Range of Coil Winding machines with automatic wire guide. Ideal for winding small transformers and solenoids.**

- Very robust and reliable
- Layer winder with automatic stop at pre-set number of turns.
- Ideal for small batch and “specials”
- Excellent repeatability and accuracy
- Can be supplied as a complete production unit, mounted on a table with wire tensioning and de-reeling devices, full safety guarding and foot pedal operation.
- Optional infinitely variable DC drive
- Constructed from robust aluminium castings and high grade steel.
- The wire guide is driven to and from by reversing dog gears via a lead screw. The traverse direction can be changed manually by a lever. The reverse carriage can be released by a quick release nut and moved to any desired position.
- The tailstock is provided with a ball race and quick release lever. The machine is provided with a universal winding spindle with cones for easy clamping of the bobbins.
- The two stage wire range is selected by a lever and adjusting wheel.
- An easily read scale shows the wire pitch setting.
- The machines are driven by a single or three phase motor incorporating an enclosed mechanical clutch and brake which is foot-pedal operated.
- The clutch can be slipped and the hand wheel used to rotate the winding shaft.
- All models are supplied with an auto-stop facility comprising of a five figure pre-determining electronic



counter and electronic brake.

	<b>BM1A</b>	<b>BM1B</b>	<b>BM1</b>	<b>BM5</b>
<b>Wire range</b>	0.06 - 1.40 mm	0.06 - 1.40 mm	0.06 - 1.40 mm	0.16 - 4.00 mm
<b>Coil diameter</b>	Max 180	Max 180	Max 180	Max 300
<b>Coil length</b>	5-190	5-190	5-190	5-220
<b>Drive</b>	1 phase, 4000 rpm	1 phase, 4000 rpm	1 phase, 4000 rpm	3 phase 1400 rpm